



## 1,5IDEALSTUCK10S Comp. A

### Safety data sheet

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Code: 1,5IDEALSTUCK10S - Comp.A 1 KG  
Product name: modified epoxy resin

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

##### 1.3 Details of the supplier of the safety data sheet

Company name: IDEAL WORK SRL  
Address: Via Kennedy, 52  
Place and country: 31030 Vallà di Riese Pio X (TV)  
Italy  
tel. 0423 /4535  
fax 0423 /748429

e-mail address for a competent person responsible for the safety data sheet: [sicurezza@idealwork.it](mailto:sicurezza@idealwork.it)

##### 1.4 Emergency telephone number

For information in an emergency

Poison center:  
National Poisons Information Service (Birmingham Unit) City Hospital  
Dudley Rd Birmingham  
Telephone: +44 121 507 4123  
Fax: +44 121 507 55 88  
Emergency telephone: 844 892 0111

#### SECTION 2. Hazards identification.

##### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

|                   |      |
|-------------------|------|
| Muta. 2           | H341 |
| Eye Irrit. 2      | H319 |
| Skin Irrit. 2     | H315 |
| Skin Sens. 1      | H317 |
| Aquatic Chronic 2 | H411 |

##### 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

Xn-N

R phrases:

36/38-43-51/53-Muta. Cat. 3 68

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

##### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

## 1,5IDEALSTUCK10S Comp. A



Signal words:

|               |  |
|---------------|--|
| <b>H341</b>   | Warning  |
| <b>H319</b>   | Suspected of causing genetic defects.                          |
| <b>H315</b>   | Causes serious eye irritation.                                 |
| <b>H317</b>   | Causes skin irritation.  |
| <b>H317</b>   | May cause an allergic skin reaction.                           |
| <b>H411</b>   | May cause an allergic skin reaction.                           |
| <b>EUH205</b> | Toxic to aquatic life with long lasting effects.               |
|               | Contains epoxy constituents. May produce an allergic reaction. |

|                  |  |
|------------------|--|
| <b>P201</b>      | Obtain special instructions before use.  |
| <b>P273</b>      | Avoid release to the environment.  |
| <b>P280</b>      | Wear protective gloves / protective clothing / eye protection / face protection. |
| <b>P302+P352</b> | IF ON SKIN: Wash with plenty of soap and water.                                  |
| <b>P308+P313</b> | IF exposed or concerned: Get medical advice / attention.                         |

**Contains:** [(tolilossi)metil]ossirano  
REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

### 2.3. Other hazards.

Information not available.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

| Identification.                                       | Conc. %.  | Classification 67/548/EEC.                         | Classification 1272/2008 (CLP).   |
|---|-----------|--|---|
| <b>REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)</b> |           |  |   |
| CAS. 25068-38-6                                       | 19,5 - 21 | Xi R36/38, Xi R43, N R51/53                        | Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411    |
| EC. 500-033-5   |           |  |   |
| INDEX. 603-074-00-8                                   |           |  |   |
| <b>[(tolilossi)metil]ossirano</b>                     |           |  |   |
| CAS. 26447-14-3                                       | 6 - 7     | Muta. Cat. 3 R68, Xi R38, Xi R43, N R51/53, Note C | Muta. 2 H341, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411, Note C |
| EC. 247-711-4   |           |  |   |
| INDEX. 603-056-00-X                                   |           |  |   |

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

**EYES:** Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

## 1,5IDEALSTUCK10S Comp. A

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

## 1,5IDEALSTUCK10S Comp. A

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Information not available.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below.

#### HAND PROTECTION

Protect hands with category III (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVA, butyl, fluoroelastomer or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

#### EYE PROTECTION

Wear hood visor or protective visor together with airtight goggles (ref. standard EN 166).

#### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

#### RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

The product must be used in well-aired environments fitted with strong localised aspiration systems, otherwise to use the personal protection equipment indicated.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

|                                  |                |
|----------------------------------|----------------|
| Appearance                       | paste          |
| Colour                           | grey           |
| Odour                            | mild           |
| Odour threshold.                 | Not available. |
| pH.                              | Not available. |
| Melting point / freezing point.  | Not available. |
| Initial boiling point.           | Not available. |
| Boiling range.                   | Not available. |
| Flash point.                     | > 60 °C.       |
| Evaporation Rate                 | Not available. |
| Flammability of solids and gases | Not available. |
| Lower inflammability limit.      | Not available. |
| Upper inflammability limit.      | Not available. |
| Lower explosive limit.           | Not available. |
| Upper explosive limit.           | Not available. |

**1,5IDEALSTUCK10S Comp. A**

|  |                    |
|--|--------------------|
| Vapour pressure.                       | 0,0075 mmHg        |
| Vapour density                         | Not available.     |
| Relative density.                      | 2,300 Kg/l         |
| Solubility                             | insoluble in water |
| Partition coefficient: n-octanol/water | Not available.     |
| Auto-ignition temperature.             | Not available.     |
| Decomposition temperature.             | Not available.     |
| Viscosity                              | Not available.     |
| Explosive properties                   | Not available.     |
| Oxidising properties                   | Not available.     |

**9.2. Other information.**

|                |          |
|----------------|----------|
| Solid content. | 100,00 % |
|----------------|----------|

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid.**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials.**

Information not available.

**10.6. Hazardous decomposition products.**

Information not available.

**SECTION 11. Toxicological information.****11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible mutagenic effects. Anyway, currently available data are insufficient to definitively prove hereditary gene alterations.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Vapour inhalation may moderately irritate the upper respiratory tract. Contact with skin may cause slight irritation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurries, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurry skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

**SECTION 12. Ecological information.**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

## 1,5IDEALSTUCK10S Comp. A

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.



CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



## SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

### Road and rail transport:

|  |                          |  |     |      |
|--|--------------------------|--|-----|------|
|  | ADR/RID Class:           | 9  | UN: | 3082 |
|  | Packing Group:           | III  |     |      |
|  | Label:                   | 9  |     |      |
|  | Nr. Kemler:              | 90   |     |      |
|  | Limited Quantity:        | 5 L  |     |      |
|  | Tunnel restriction code: | (E)  |     |      |
|  | Proper Shipping Name:    | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN);<br>[(tolilossi)metil]ossirano) |     |      |

### Carriage by sea (shipping):

|  |                       |  |     |      |
|--|-----------------------|--|-----|------|
|  | IMO Class:            | 9  | UN: | 3082 |
|  | Packing Group:        | III  |     |      |
|  | Label:                | 9  |     |      |
|  | EMS:                  | F-A, S-F   |     |      |
|  | Marine Pollutant:     | YES  |     |      |
|  | Proper Shipping Name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN);<br>[(tolilossi)metil]ossirano) |     |      |

## 1,5IDEALSTUCK10S Comp. A

### Transport by air:



|                         |  |                   |       |
|-------------------------|--|-------------------|-------|
| IATA:                   | 9  | UN:               | 3082  |
| Packing Group:          | III  |                   |       |
| Label:                  | 9  |                   |       |
| Cargo:                  |  |                   |       |
| Packaging instructions: | 964  | Maximum quantity: | 450 L |
| Pass.:                  |  |                   |       |
| Packaging instructions: | 964  | Maximum quantity: | 450 L |
| Special Instructions:   | A97, A158  |                   |       |
| Proper Shipping Name:   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN);<br>[(tolilossi)metil]ossirano) |                   |       |

**Packaging: 1 Kg metal tin – approval not required**

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 9ii

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point. 3

Substances in Candidate List (Art. 59 REACH).  
None.

Substances subject to authorisation (Annex XIV REACH).  
None.

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:  
None.

Substances subject to the Rotterdam Convention:  
None.

Substances subject to the Stockholm Convention:  
None.

### Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                      |                                    |
|----------------------|------------------------------------|
| <b>Muta. 2</b>       | Germ cell mutagenicity, category 2 |
| <b>Eye Irrit. 2</b>  | Eye irritation, category 2         |
| <b>Skin Irrit. 2</b> | Skin irritation, category 2        |
| <b>Skin Sens. 1</b>  | Skin sensitization, category 1     |



# IDEAL WORK

Revision nr. 2

Dated 15/06/2015

Printed on March 7, 2018

Page n. 8/9

## 1,5IDEALSTUCK10S Comp. A

|                          |  |
|--------------------------|--|
| <b>Aquatic Chronic 2</b> | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| <b>H341</b>              | Suspected of causing genetic defects.                              |
| <b>H319</b>              | Causes serious eye irritation.                                     |
| <b>H315</b>              | Causes skin irritation.  |
| <b>H317</b>              | May cause an allergic skin reaction.                               |
| <b>H411</b>              | Toxic to aquatic life with long lasting effects.                   |
| <b>EUH205</b>            | Contains epoxy constituents. May produce an allergic reaction.     |

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

|                     |   |
|---------------------|---|
| <b>R36/38</b>       | IRRITATING TO EYES AND SKIN.  |
| <b>R38</b>          | IRRITATING TO SKIN.   |
| <b>R43</b>          | MAY CAUSE SENSITISATION BY SKIN CONTACT.  |
| <b>R51/53</b>       | TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. |
| <b>Muta. Cat. 3</b> | Mutagenicity, category 3.   |
| <b>R68</b>          | POSSIBLE RISK OF IRREVERSIBLE EFFECTS.  |

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. The Merck Index. - 10th Edition
9. Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.



## 1,5IDEALSTUCK10S Comp. A

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 08 / 09 / 10 / 11 / 12 / 16.