

Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 1/7

DISAT.VERT

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Place and country

Code: DISAT.VERT

Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Deactivator for vertical surfaces

1.3 Details of the supplier of the safety data sheet

Company name IDEAL WORK SRL Address Via Kennedy, 52

31030 Valla di Riese Pio X (TV)

Italy

tel. 0423 /4535 fax 0423 /748429

e-mail address for a competent person, responsible for the safety data sheet

sicurezza@idealwork.it

1.4 Emergency telephone number

For information in an emergency Poison center:

National Poisons Information Service (Birmingham

Unit) City Hospital Dudley Rd Birmingham Telephone: +44 121 507 4123 Fax: +44 121 507 55 88

Emergency telephone: 844 892 0111

SECTION 2. Hazards identification.

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.



Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 2/7

DISAT.VERT

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02 GHS07 GHS08 GHS09

- Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3. Composition/information on ingredients.

- 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

EINECS: 265-151-9 Index number: 649-328-00-1	Naphtha (petroleum), hydrotreated light Xn R65; FR11; N R51/53 R66-67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-50%
CAS: 68855-54-9 EINECS: 272-489-0	Kieselguhr, soda ash flux-calcined Xn R48/20 ♦ STOT RE 2, H373	10-<25%
CAS: 77-92-9 EINECS: 201-069-1	citric acid Xi R36	10-<20%

· Additional information:

Benzene (CAS 71-43-2) < 0,1%

For the wording of the listed risk phrases refer to section 16.

SECTION 4. First aid measures.

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.



Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 3/7

DISAT.VERT

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

SECTION 5. Firefighting measures.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6. Accidental release measures.

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. Handling and storage.

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8. Exposure controls/personal protection.

- · Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

· Protection of hands:





Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 4/7

DISAT.VERT

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0,35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

KCL Camatril ®: 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9. Physical and chemical properties.

General Information	
Appearance:	
Form:	Fluid
Colour:	Different according to colouring
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	107 °C
Flash point:	≤ 21 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosi- air/vapour mixtures are possible.
Explosion limits:	
Lower:	0,9 Vol %
Upper:	6,8 Vol %
Vapour pressure:	Not determined.
Density at 20 °C:	1 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.



DISAT.VERT

Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 5/7

· Solvent content:

Organic solvents: 38,7 %

9.2 Other information No further relevant information available.

SECTION 10. Stability and reactivity.

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11. Toxicological information.

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

SECTION 12. Ecological information.

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13. Disposal considerations.

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue		
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 02 00	wastes from MFSU of other coatings (including ceramic materials)		
08 02 99	wastes not otherwise specified		

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.



DISAT.VERT

Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 6/7

SECTION 14. Transport information.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR	1866 RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS
IMDG	RESIN SOLUTION (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT
IATA	RESIN SOLUTION
14.3 Transport hazard class(es) ADR, IMDG	
Class Label	3 Flammable liquids. 3
Class Label	3 Flammable liquids.
14.4 Packing group	1070
ADR, IMDG, IATA	II.
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light Yes Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler): EMS Number:	33 F-E, <u>S-E</u>
14.7 Transport in bulk according to Ann of MARPOL73/78 and the IBC Code	nex II Not applicable.
Transport/Additional information:	300000000000000000000000000000000000000
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 500
Transport category	2
Tunnel restriction code	D/E
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 500 i
UN "Model Regulation":	UN1866, RESIN SOLUTION,

Packaging: 5 KG BUCKET - APPROVAL 1A2/Y1,4/100 - Ø 19,8 cm x 21,4cmH - Weight 0.554 KG



DISAT.VERT

Revision nr. 1

Dated 18/12/2014

Printed on 18/12/2014

Page n. 7/7

SECTION 15. Regulatory information.

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16. Other information.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- May cause damage to organs through prolonged or repeated exposure. H373
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R36 Irritating to eyes.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- Department issuing MSDS: Forschung und Entwicklung
- Contact: Hr. Herrfeld
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.