

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 6,7IDEALCOLOR80
Product name: IDEALCOLOR 80 comp. B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use catalizzatore per vernice poliuretanica.

1.3. Details of the supplier of the safety data sheet

Name: IDEALWORK SRL
Full address: via Kennedy 52
District and Country: 31030 Vallà di Riese Pio X (TV)
Italy
Tel. +39 0423 / 4535
Fax +39 0423 / 748429

e-mail address of the competent person
responsible for the Safety Data Sheet
Product distribution by

sicurezza@idealwork.it
idealwork s.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to

Poison center:
National Poisons Information Service (Birmingham Unit) City Hospital
Dudley Rd Birmingham
Telephone: +44 121 507 4123
Fax: +44 121 507 55 88
Emergency telephone: 844 892 0111

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Resp. Sens. 1	H334

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

F-Xn

R phrases:

11-20/21-42

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.





IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 2/10

IDEALCOLOR 80 comp. B

Signal words:

Danger

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EUH204

Contains isocyanates. May produce an allergic reaction.

EUH208

Contains:

TOLUENE-2,4-DI-ISOCYANATE

May produce an allergic reaction.

P210

Keep away from heat / sparks / open flames / hot surfaces. No smoking.

P264

Wash . . . thoroughly after handling.

P280

Wear protective gloves / protective clothing / eye protection / face protection.

P304+P341

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+P311

If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P370+P378

In case of fire: Use . . . for extinction.

Contains:

TOLUENE-2,4-DI-ISOCYANATE

2.3. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.**XYLENE (MIXTURE OF ISOMERS)**

CAS. 1330-20-7

Conc. %. 9 - 10,5

Classification 67/548/EEC. R10, Xn R20/21, Xi R38, Note C

Classification 1272/2008 (CLP). Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

EC. 215-535-7

INDEX. 601-022-00-9

1-METHOXY-2-PROPANOL ACETATE

CAS. 108-65-6

Conc. %. 9 - 10,5

Classification 67/548/EEC. R10

Classification 1272/2008 (CLP). Flam. Liq. 3 H226

EC. 203-603-9

INDEX. 607-195-00-7

TOLUENE-2,4-DI-ISOCYANATE

CAS. 91-08-7

Conc. %. 0,5 - 0,6

Classification 67/548/EEC. Carc. Cat. 3 R40, R52/53, T+ R26, Xn R42/43, Xi R36/37/38, Note 2 C

Classification 1272/2008 (CLP). Carc. 2 H351, Acute Tox. 2 H330, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Aquatic Chronic 3 H412, Note 2 C

EC. 202-039-0

INDEX. 615-006-00-4

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice



IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 3/10

IDEALCOLOR 80 comp. B

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.



IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 4/10

IDEALCOLOR 80 comp. B

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

TLV-ACGIH ACGIH 2012

1-METHOXY-2-PROPANOL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	274	50	548	100	
OEL	IRL	275	50	550	100	SKIN
OEL	EU	275	50	550	100	SKIN

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	220	50	441	100	
OEL	IRL	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

TOLUENE-2,4-DI-ISOCYANATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	0,02		0,07		
OEL	IRL	0,001		0,003		

TLV-ACGIH	0,036	0,005	0,14	0,02
-----------	-------	-------	------	------

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitril or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an AX or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.**9.1. Information on basic physical and chemical properties.**

Appearance	liquid
Colour	transparent
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	37 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,960 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.



IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 6/10

IDEALCOLOR 80 comp. B

Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL ACETATE: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.
TOLUENE-2,4-DI-ISOCYANATE: reacts with hot water and alcohols, decomposing and releasing carbon dioxide. With tertiary amines and strong bases it polymerises rapidly, developing heat.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

1-METHOXY-2-PROPANOL ACETATE: may react violently with oxidising agents and strong acids and alkaline metals.
TOLUENE-2,4-DI-ISOCYANATE: With tertiary amines and strong bases it polymerises rapidly, developing heat. Reacts violently, developing heat with: acetyl chloride, amines, bases, ethanol, methanol, oxidants, phenol, forms explosive mixtures with hot air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL ACETATE: store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.
TOLUENE-2,4-DI-ISOCYANATE: avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials.

1-METHOXY-2-PROPANOL ACETATE: oxidising agents, strong acids and alkaline metals.
TOLUENE-2,4-DI-ISOCYANATE: water, acids, alkalis, amines and strong oxidising agents.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

TOLUENE-2,4-DI-ISOCYANATE: carbon oxides, hydrogen cyanide, nitrous gases.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.



IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 7/10

IDEALCOLOR 80 comp. B

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

1-METHOXY-2-PROPANOL ACETATE: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral). 3523 mg/kg Rat

LD50 (Dermal). 4350 mg/kg Rabbit

LC50 (Inhalation). 26 mg/l/4h Rat

1-METHOXY-2-PROPANOL ACETATE

LD50 (Oral). 8530 mg/kg Rat

LD50 (Dermal). > 5000 mg/kg Rat

SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil, sewers and waterways. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.


CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.


SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.


Road and rail transport:

	ADR/RID Class:	3	UN:	1263
	Packing Group:	II		
	Label:	3		
	Nr. Kemler:	33		
	Limited Quantity:	5 L		
	Tunnel restriction code:	(D/E)		
	Proper Shipping Name:	PAINT		
	Special Provision:	640D		

Carriage by sea (shipping):

	IMO Class:	3	UN:	1263
	Packing Group:	II		
	Label:	3		
	EMS:	F-E ,	<u>S-E</u>	
	Marine Pollutant:	NO		
	Proper Shipping Name:	PAINT		

Transport by air:

	IATA:	3	UN:	1263
	Packing Group:	II		
	Label:	3		
	Cargo:			
	Packaging instructions:	364	Maximum quantity:	60 L
	Pass.:			
	Packaging instructions:	353	Maximum quantity:	5 L
	Special Instructions:	A3, A72		
	Proper Shipping Name:	PAINT		

Packaging:

1,7 LT METAL BUCKET – APPROVAL NOT REQUESTED – Ø 16.2 cm x 16cmH – Weight 0,300 KG

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 7b

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.



IDEALWORK

Revision nr. 3

Dated 7/7/2015

Printed on 07/07/2015

Page n. 9/10

IDEALCOLOR 80 comp. B

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H330	Fatal if inhaled.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
EUH204	Contains isocyanates. May produce an allergic reaction.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R11	HIGHLY FLAMMABLE.

IDEALCOLOR 80 comp. B

R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R26	VERY TOXIC BY INHALATION.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R38	IRRITATING TO SKIN.
Carc. Cat. 3	Carcinogenicity, category 3.
R40	LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.
R42	MAY CAUSE SENSITIZATION BY INHALATION.
R42/43	MAY CAUSE SENSITIZATION BY INHALATION AND SKIN CONTACT.
R52/53	HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. The Merck Index. - 10th Edition
9. Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.