

### Safety data sheet

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name **IDEALPU-WB EASY Part. B**

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Component B for two-component water-based laquer.**

##### 1.3 Details of the supplier of the safety data sheet

Company name **IDEAL WORK SRL**  
Address **Via Kennedy, 52**  
Place and country **31030 Vallà di Riese Pio X (TV)  
Italy**  
**tel. +39 0423 /4535**  
**fax +39 0423 /748429**

e-mail address for a competent person,  
responsible for the safety data sheet

[sicurezza@idealwork.it](mailto:sicurezza@idealwork.it)

##### 1.4 Emergency telephone number

For information in an emergency

**Poison center:**  
**National Poisons Information Service (Birmingham  
Unit) City Hospital**  
**Dudley Rd Birmingham**  
**Telephone: +44 121 507 4123**  
**Fax: +44 121 507 55 88**  
**Emergency telephone: 844 892 0111**

#### SECTION 2. Hazards identification

##### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4	H332	Harmful if inhaled.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Warning**

## IDEALPU-WB EASY Part. B

### Hazard statements:

<b>H332</b>	Harmful if inhaled.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH204</b>	Contains isocyanates. May produce an allergic reaction.
<b>EUH208</b>	Contains: HEXAMETHYLENE-DI-ISOCYANATE May produce an allergic reaction.

### Precautionary statements:

<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.
<b>P280</b>	Wear protective gloves.
<b>P312</b>	Call a POISON CENTRE or a doctor if you feel unwell.
<b>P362+P364</b>	Take off contaminated clothing and wash it before reuse.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.

<b>Contains:</b>	HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON HDI HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON IPDI HEXAMETHYLENE-DI-ISOCYANATE
------------------	--

### VOC (Directive 2004/42/EC) :

#### Two-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :	113,24
Limit value:	140,00
- Catalysed with :	500,00 % IDEAL PU WB Comp.A (10:2)

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

### 3.2. Mixtures

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON HDI</b> CAS 666723-27-9	20 ≤ x < 25	Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 3 H412
EC INDEX -		
<b>HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER</b> CAS 3779-63-3	20 ≤ x < 30	Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317
EC 223-242-0 INDEX -		
<b>HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON IPDI</b> CAS 1574548-27-8	9 ≤ x < 20	STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 3 H412

## IDEALPU-WB EASY Part. B

EC

INDEX -

**HEXAMETHYLENE-DI-ISOCYANATE**

CAS 822-06-0

0 ≤ x &lt; 0,25

Acute Tox. 1 H330, Acute  
Tox. 4 H302, Eye Irrit. 2  
H319, Skin Irrit. 2 H315,  
STOT SE 3 H335, Resp.  
Sens. 1 H334, Skin Sens. 1  
H317, Note 2

EC 212-485-8

INDEX 615-011-00-1

Reg. no. 01-2119457571-37-XXXX

### SECTION 4. First aid measures

**4.1. Description of first aid measures**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

### SECTION 5. Firefighting measures

**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

## IDEALPU-WB EASY Part. B

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
NOR	Norge	Veiledning om Administrative normer for forurensning i arbeidsatmosfære
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
	TLV-ACGIH	ACGIH 2016

### HEXAMETHYLENE-DI-ISOCYANATE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU		0,005		0,005
VLA	ESP		0,005		
VLEP	FRA	0,075		0,15	
WEL	GBR	0,02		0,07	
TLV	NOR		0,005		0,01
MAK	SWE		0,005		
TLV-ACGIH			0,005		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

## IDEALPU-WB EASY Part. B

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	transparent
Odour	typical
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 61 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower flammability limit	Not available
Upper flammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available

## IDEALPU-WB EASY Part. B

Oxidising properties Not available

### 9.2. Other information

VOC (Directive 2004/42/EC) : 30,00 % - 345,00 g/litre  
VOC (volatile carbon) : 15,79 % - 181,59 g/litre  
Appearance Liquid

## SECTION 10. Stability and reactivity

HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON HDI

Exothermic reaction with amines and alcohols with water gradual development  
CO2 increase pressure in closed containers; danger of bursting.

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

Information not available

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:10,00 mg/l

LD50 (Oral) of the mixture:Not classified (no significant component)

LD50 (Dermal) of the mixture:Not classified (no significant component)

HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON HDI

> 5000 mg/kg OECD TG 423

LD50 (Oral)

0,39 mg/l/4h Ratto, femmina

LC50 (Inhalation)

HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON IPDI

> 2000 mg/kg OECD TG 423

LD50 (Oral)

> 5 mg/l/4h Linee Guida 403 per il Test dell'OECD

LC50 (Inhalation)

## IDEALPU-WB EASY Part. B

### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin May produce an allergic reaction. Contains: HEXAMETHYLENE-DI-ISOCYANATE

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

May cause respiratory irritation

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### HYDROPHILIC ALIPHATIC POLYISOCYANATE BASED ON HDI

Reacts with water in correspondence of the contact surface with the development of CO<sub>2</sub>

forming a solid reaction product, insoluble high melting point (polyurea). This reaction is accelerated by surfactants (eg. Liquid soap) and water-soluble solvents. According to the experience gained to date, polyurea is inert and non-degradable.

#### 12.1. Toxicity

HYDROPHILIC ALIPHATIC  
POLYISOCYANATE BASED  
ON HDI

LC50 - for Fish

35,2 mg/l/96h Danio Rerio (pesce zebra)

EC50 - for Crustacea

> 100 mg/l/48h Saggio sulla specie: Daphnia magna

EC50 - for Algae / Aquatic  
Plants

> 72 mg/l/72h Testato su: alghe

HYDROPHILIC ALIPHATIC  
POLYISOCYANATE BASED  
ON IPDI

LC50 - for Fish

35,2 mg/l/96h Danio rerio (pesce zebra)

EC50 - for Algae / Aquatic  
Plants

72 mg/l/72h OECD TG 201

#### 12.2. Persistence and degradability

HYDROPHILIC ALIPHATIC  
POLYISOCYANATE BASED  
ON HDI

NOT rapidly degradable

HYDROPHILIC ALIPHATIC  
POLYISOCYANATE BASED  
ON IPDI

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

Information not available

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number

Not applicable

### 14.2. UN proper shipping name

Not applicable

### 14.3. Transport hazard class(es)

Not applicable

### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Not applicable

### 14.6. Special precautions for user

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

#### Product

Point 3

#### Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

#### Substances subject to authorisation (Annex XIV REACH)

None

#### Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

#### Substances subject to the Rotterdam Convention:

None



Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two-pack performance coatings.

### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 1</b>	Acute toxicity, category 1
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Resp. Sens. 1</b>	Respiratory sensitization, category 1
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H330</b>	Fatal if inhaled.
<b>H302</b>	Harmful if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H334</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH204</b>	Contains isocyanates. May produce an allergic reaction.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006

## IDEALPU-WB EASY Part. B

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### Changes to previous review:

The following sections were modified:

01.