	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 1/12

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: IDEALPU78-SUPER MATT (part B)  
Product name: CATALYST

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: CATALYST

#### 1.3 Details of the supplier of the safety data sheet

Company name: IDEAL WORK SRL  
Address: Via Kennedy, 52  
Place and country: 31030 Vallà di Riese Pio X (TV)  
Italy

tel. 0423 /4535

fax 0423 /748429

e-mail address for a competent person,  
responsible for the safety data sheet

[sicurezza@idealwork.it](mailto:sicurezza@idealwork.it)

#### 1.4 Emergency telephone number

For information in an emergency

Poison center:  
National Poisons Information Service (Birmingham  
Unit) City Hospital  
Dudley Rd Birmingham  
Telephone: +44 121 507 4123  
Fax: +44 121 507 55 88  
Emergency telephone: 844 892 0111

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Asp. Tox. 1	H304
Resp. Sens. 1	H334
Skin Sens. 1	H317

##### 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

Xn

R phrases:

10-20/21-36-42/43-65


The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 2/12

Signal words: Danger

Hazard statements:

**H226** Flammable liquid and vapour.  
**H332** Harmful if inhaled.  
**H304** May be fatal if swallowed and enters airways.  
**H334** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
**H317** May cause an allergic skin reaction.  
**EUH204** Contains isocyanates. May produce an allergic reaction.  
**EUH208** Contains:

HEXAMETHYLENE-DI-ISOCYANATE

May produce an allergic reaction.

Precautionary statements:

**P210** Keep away from heat / sparks / open flames / hot surfaces. No smoking.  
**P233** Keep container tightly closed.  
**P280** Wear protective gloves / protective clothing / eye protection / face protection.  
**P301+P310** IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.  
**P304+P341** IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
**P370+P378** In case of fire: Use . . . for extinction.

**Contains:** SOLVENT NAPHTA (PETROLEUM), LIGHT AROM  
 ALIPHATIC POLYISOCYANATE

### 2.3. Other hazards.

Information not available.

## SECTION 3. Composition/information on ingredients.


### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
<b>ALIPHATIC POLYISOCYANATE</b>			
CAS. 28182-81-2	30 - 50	Xn R20, Xn R42/43	Acute Tox. 4 H332, Resp. Sens. 1 H334, Skin Sens. 1 H317
EC. -			
INDEX. -			
<b>SOLVENT NAPHTA (PETROLEUM), LIGHT AROM</b>			
CAS. 64742-95-6	20 - 30	Xn R65, Note P	Asp. Tox. 1 H304, Note P
EC. 265-199-0			
INDEX. 649-356-00-4			
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>			
CAS. 108-65-6	10 - 20	R10, Xi R36	Flam. Liq. 3 H226
EC. 203-603-9			
INDEX. 607-195-00-7			
<b>XYLENE (MIXTURE OF ISOMERS)</b>			
CAS. 1330-20-7	5 - 10	R10, Xn R20/21, Xi R38, Note C	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C
EC. 215-535-7			
INDEX. 601-022-00-9			

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 3/12

#### ETHYLBENZENE

CAS. 100-41-4

1 - 5

F R11, Xn R20

Flam. Liq. 2 H225, Acute Tox. 4 H332

EC. 202-849-4

INDEX. 601-023-00-4

#### HEXAMETHYLENE-DI-ISOCYANATE

CAS. 822-06-0

0 - 0,5

T R23, Xn R42/43, Xi R36/37/38, Note 2

Acute Tox. 1 H330, Acute Tox. 4 H302, Skin Corr. 1C H314, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2

EC. 212-485-8

INDEX. 615-011-00-1

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.


### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 4/12

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).


Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

	<b>IDEAL WORK</b>				Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>				Stampata il 26/05/2015 Pagina n. 5/12

2000/39/EC.  
TLV-ACGIH ACGIH 2012

#### 2-METHOXY-1-METHYLETHYL ACETATE

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	275	50	550	100	SKIN
OEL	IRL	275	50	550	100	SKIN
WEL	UK	274	50	548	100	

#### XYLENE (MIXTURE OF ISOMERS)

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		434	100	651	150	
OEL	EU	221	50	442	100	SKIN
OEL	IRL	221	50	442	100	SKIN
WEL	UK	220	50	441	100	

#### ETHYLBENZENE

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		87	20			
OEL	EU	442	100	884	200	SKIN
OEL	IRL	442	100	884	200	SKIN
WEL	UK	441	100	552	125	SKIN

#### HEXAMETHYLENE-DI-ISOCYANATE

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		0,034	0,005			
OEL	IRL	0,02		0,07		
WEL	UK	0,02		0,07		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.


Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 6/12

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.


## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	transparent
Odour	di esteri
Odour threshold.	Not available.
pH.	N.A.
Melting point / freezing point.	Not available.
Initial boiling point.	140 °C.
Boiling range.	Not available.
Flash point.	30 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	ca. 0,95
Solubility	insoluble
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	330 °C.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

VOC (Directive 1999/13/EC) :	51,25 %
VOC (volatile carbon) :	37,81 %

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 7/12

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL ACETATE: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.  
HEXAMETHYLENE-DI-ISOCYANATE: decomposes at 255°C. Polymerises at temperatures above 200°C.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

1-METHOXY-2-PROPANOL ACETATE: may react violently with oxidising agents and strong acids and alkaline metals.

ETHYLBENZENE: reacts violently with strong oxidising agents and attacks various types of plastics. Can form explosive mixtures with the air.

HEXAMETHYLENE-DI-ISOCYANATE: can cause explosive reactions with alcohols and bases. Can react violently with: alcohols, amines, strong bases, oxidant agents, strong acids, water.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL ACETATE: store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.

HEXAMETHYLENE-DI-ISOCYANATE: avoid exposure to high temperatures, moisture.

### 10.5. Incompatible materials.

1-METHOXY-2-PROPANOL ACETATE: oxidising agents, strong acids and alkaline metals.

HEXAMETHYLENE-DI-ISOCYANATE: alcohols, carboxylic acids, amines and strong bases.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE: methane, styrene, hydrogen, ethane.

HEXAMETHYLENE-DI-ISOCYANATE: nitric oxide, hydrogen cyanide.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.


Acute effects: inhalation of this product is harmful.

Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness. In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurries, ulcerations and exudative

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 8/12

phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

1-METHOXY-2-PROPANOL ACETATE: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

ETHYLBENZENE: like the benzene homologues, may exert an effect on the CNS with depression, narcosis, often preceded by dizziness and accompanied by headache. It is irritating to the skin, conjunctivae and respiratory apparatus.

XYLENE (MIXTURE OF ISOMERS)  
 LD50 (Oral). 3523 mg/kg Rat  
 LD50 (Dermal). 4350 mg/kg Rabbit  
 LC50 (Inhalation). 26 mg/l/4h Rat

2-METHOXY-1-METHYLETHYL ACETATE  
 LD50 (Oral). 8530 mg/kg Rat  
 LD50 (Dermal). > 5000 mg/kg Rat

ETHYLBENZENE  
 LD50 (Oral). 3500 mg/kg Rat  
 LD50 (Dermal). 15354 mg/kg Rabbit  
 LC50 (Inhalation). 17,2 mg/l/4h Rat

HEXAMETHYLENE-DI-ISOCYANATE  
 LC50 (Inhalation). 0,124 mg/l/4h Rat

## SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.


Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways.



	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 9/12

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

### Road and rail transport:



ADR/RID Class:	3	UN:	1263
Packing Group:	III		
Label:	3		
Nr. Kemler:	30		
Limited Quantity:	5 L		
Tunnel restriction code:	(D/E)		
Proper Shipping Name:	PAINT		
Special Provision:	640E		

### Carriage by sea (shipping):



IMO Class:	3	UN:	1263
Packing Group:	III		
Label:	3		
EMS:	F-E ,	<u>S-E</u>	
Marine Pollutant:	NO		
Proper Shipping Name:	PAINT		

### Transport by air:



IATA:	3	UN:	1263
Packing Group:	III		
Label:	3		
Cargo:			
Packaging instructions:	366	Maximum quantity:	220 L
Pass.:			
Packaging instructions:	355	Maximum quantity:	60 L
Special Instructions:	A3, A72, A192		
Proper Shipping Name:	PAINT		


### Packaging:

**7,5 KG PACKAGE**

**PART "B" = 2,5 KG – APPROVAL 1A1/Y1,2/100 – Ø 17 cm x 16cmH – Peso 0,75 KG**

**1 KG PACKAGE**

**PART "B" = 0,334 KG – APPROVAL NOT REQUIRED**

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 10/12

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.  
Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).  
None.

Substances subject to authorisation (Annex XIV REACH).  
None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:  
None.

Substances subject to the Rotterdam Convention:  
None.

Substances subject to the Stockholm Convention:  
None.

#### Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.


### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 1	Acute toxicity, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Skin Corr. 1C	Skin corrosion, category 1C
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 11/12

<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H334</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b>H317</b>	May cause an allergic skin reaction.
<b>EUH204</b>	Contains isocyanates. May produce an allergic reaction.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:


<b>R10</b>	FLAMMABLE.
<b>R11</b>	HIGHLY FLAMMABLE.
<b>R20</b>	HARMFUL BY INHALATION.
<b>R20/21</b>	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
<b>R23</b>	TOXIC BY INHALATION.
<b>R36</b>	IRRITATING TO EYES.
<b>R36/37/38</b>	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
<b>R38</b>	IRRITATING TO SKIN.
<b>R42/43</b>	MAY CAUSE SENSITIZATION BY INHALATION AND SKIN CONTACT.
<b>R65</b>	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament

	<b>IDEAL WORK</b>	Revisione n. 2 Data revisione 26/5/2015
	<b>IDEALPU78-SUPER MATT (part B)</b>	Stampata il 26/05/2015 Pagina n. 12/12

7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition
10. Handling Chemical Safety
11. Niosh - Registry of Toxic Effects of Chemical Substances
12. INRS - Fiche Toxicologique (toxicological sheet)
13. Patty - Industrial Hygiene and Toxicology
14. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
15. ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

08 / 15.