

Revision nr. 1

Dated 02/10/2018

Printed on October 20, 2018

age n. 1/9

# PUROMETALLO-PRIMER

## **Safety Data Sheet**

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** Code: Product name

PUROMETALLO-PRIMER

 1.2. Relevant identified uses of the substance or mixture and uses advised against

 Intended use
 Single component waterborne acrylic primer for microcement

### 1.3 Details of the supplier of the safety data sheet

Company name Address Place and country	IDEAL WORK SRL Via Kennedy, 52 31030 Vallà di Riese Pio X (TV) Italy tel. +39 0423 /4535 fax +39 0423 /748429
e-mail address for a competent person, responsible for the safety data sheet	sicurezza@idealwork.it
1.4 Emergency telephone number	

For information in an emergency

Poison center: National Poisons Information Service (Birmingham Unit) City Hospital Dudley Rd Birmingham Telephone: +44 121 507 4123 Fax: +44 121 507 55 88 Emergency telephone: 844 892 0111

## **SECTION 2. Hazards identification.**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830. Hazard classification and indication:

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

	May produce an allergic reaction.
Hazard statements: EUH210 EUH208	Safety data sheet available on request. Contains:, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)
Signal words:	-
Hazard pictograms:	

-

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## **SECTION 3. Composition/information on ingredients.**

3.1. Substances



Revision nr. 1

Dated 02/10/2018

## PUROMETALLO-PRIMER

Printed on October 20, 2018

age n. 2/9

3.2. Mixtures Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Mixture of: 5-chloro-2-methyl-2H- isothiazol-3-one; 2-methyl-2H- isothiazol-3-one (3: 1)		
CAS 55965-84-9	0 ≤ x < 0,0015	Acute Tox. 2 H330, Acute Tox. 3 H311, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10
EC -		
INDEX 613-167-00-5		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures

Not specifically necessary. Observance of good industrial hygiene is recommended.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



Revision nr. 1

Dated 02/10/2018

## **PUROMETALLO-PRIMER**

Printed on October 20, 2018

Page n. 3/9

## **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection.**

### 8.1. Control parameters

**Regulatory References:** 

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
NOR	Norge	Veiledning om Administrative normer for forurensning i arbeidsatmosfære
POL	Polska	ROZPORŽADZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
SVN	Slovenija	Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o
		varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
	TLV-ĂCGIH	ACGIH 2018

### TITANIUM DIOXIDE

Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	10						
VLEP	FRA	10						
WEL	GBR	4						
TLV	GRC		10					
TLV	NOR	5						
NDS	POL	10				INHAL		
MAK	SWE	5						
TLV-ACGIH		10						
Predicted no-effect concen	tration - PNEC							
Normal value in fresh water	-			0,184	mg	ı/I		
Normal value in marine wat	er			0,0184	mg	//		
Normal value for fresh wate	er sediment			1000	mg	/kg/dw		
Normal value for marine wa	ater sediment			100	mg	/kg/dw		
Normal value for water, inte	ermittent release			0,193	mg	ı/I		
Normal value of STP micro	organisms			100	mg	ı/I		
Normal value for the terrest	rial compartment			100	mg	/kg/dw		
Health - Derived no-ef		OMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				700 mg/kg/d		Systemic		Systemic
Inhalation			10 mg/m3				10 mg/m3	



Revision nr. 1 Dated 02/10/2018

Printed on October 20, 2018

## PUROMETALLO-PRIMER

age n. 4/9

Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	4				INHAL		
MAK	DEU	4				INHAL		
MV	SVN	4				INHAL		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	4 mg/m3

Inhalation

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 97 mg/m3

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Revision nr. 1

Dated 02/10/2018

#### Printed on October 20, 2018

age n. 5/9

## PUROMETALLO-PRIMER

## **SECTION 9.** Physical and chemical properties.

9.1. Information on bas	sic physical	and chemical	properties
••••••••••••••••			p

9.1. Information on basic physical and che	mical properties
Appearance	dense liquid
Colour	grey
Odour	characteristic
Odour threshold	Not available
рН	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,17
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available
9.2. Other information	
VOC (Directive 2010/75/EC) :	0,82 % - 9,54 g/litre
VOC (volatile carbon) :	0,50 % - 5,80 g/litre
· · · · · · · · · · · · · · · · · · ·	,

## **SECTION 10. Stability and reactivity.**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

### **SECTION 11. Toxicological information.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information Information not available

Information on likely routes of exposure Information not available



PUROMETALLO-PRIMER

Revision nr. 1 Dated 02/10/2018

Printed on October 20, 2018

age n. 6/9

Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available

Interactive effects

Information not available

ACUTE TOXICITY LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: Not classified (no significant component) LD50 (Dermal) of the mixture: Not classified (no significant component)

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1) LD50 (Oral) 53 mg/kg Ratto LD50 (Dermal) > 2000 mg/kg ratto LC50 (Inhalation) 330 mg/m3 4h Ratto

SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION May produce an allergic reaction.Contains:Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)

<u>GERM CELL MUTAGENICITY</u> Does not meet the classification criteria for this hazard class

<u>CARCINOGENICITY</u> Does not meet the classification criteria for this hazard class

<u>REPRODUCTIVE TOXICITY</u> Does not meet the classification criteria for this hazard class

<u>STOT - SINGLE EXPOSURE</u> Does not meet the classification criteria for this hazard class

<u>STOT - REPEATED EXPOSURE</u> Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD Does not meet the classification criteria for this hazard class

## **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1) LC50 - for Fish

EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants

0,19 mg/l/96h Pesce Oncorhynchus mykiss 0,16 mg/l/48h Dafnia 0,018 mg/l/72h Alghe - Selenastrum capricornutum

### 12.2. Persistence and degradability

Information not available



Revision nr. 1

Dated 02/10/2018

## **PUROMETALLO-PRIMER**

Printed on October 20, 2018

age n. 7/9

## 12.3. Bioaccumulative potential

Information not available

### **12.4. Mobility in soil** Information not available

## 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

## **SECTION 13.** Disposal considerations.

### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number Not applicable

**14.2. UN proper shipping name** Not applicable

14.3. Transport hazard class(es) Not applicable

14.4. Packing group Not applicable

**14.5. Environmental hazards** Not applicable

**14.6. Special precautions for user** Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Information not relevant

## **SECTION 15.** Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None <u>Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006</u> None

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None



Revision nr. 1

Dated 02/10/2018

## **PUROMETALLO-PRIMER**

Printed on October 20, 2018

age n. 8/9

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

Healthcare controls Information not available

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Aguta taviaity, astagony 2
Acute TOX. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Skin Corr. 1B	Skin corrosion, category 1B
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H330	Fatal if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level - EmS: Emergency Schedule
- Erris. Emergency Schedule - GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**IDEAL** WORK

Revision nr. 1

Dated 02/10/2018

## Printed on October 20, 2018

age n. 9/9

## PUROMETALLO-PRIMER

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
   Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.