

## SUPER-SEALER NEW

### Safety data sheet

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Code: SUPER-SEALER NEW  
Product name: --

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Resin solution

##### 1.3 Details of the supplier of the safety data sheet

Company name: IDEAL WORK SRL  
Address: Via Kennedy, 52  
Place and country: 31030 Vallà di Riese Pio X (TV)  
Italy  
tel. 0423 /4535  
fax 0423 /748429

e-mail address for a competent person responsible for the safety data sheet

[sicurezza@idealwork.it](mailto:sicurezza@idealwork.it)

##### 1.4 Emergency telephone number









For information in an emergency

Poison center:  
National Poisons Information Service (Birmingham Unit) City Hospital  
Dudley Rd Birmingham  
Telephone: +44 121 507 4123  
Fax: +44 121 507 55 88  
Emergency telephone: 844 892 0111

#### SECTION 2. Hazards identification.

##### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Warning, Acute Tox. 4, Harmful in contact with skin.
-  Warning, Acute Tox. 4, Harmful if inhaled.
-  Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.
-  Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

##### 2.2. Label elements

Symbols:



Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H312+H332 Harmful in contact with skin or if inhaled.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

## SUPER-SEALER NEW

H315 Causes skin irritation.

H319 Causes serious eye irritation.

**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

**Special Provisions:**

None

**Contents**

n-butyl acetate

toluene

xylene

ethylbenzene

**Special provisions according to Annex XVII of REACH and subsequent amendments:**

None

**2.3. Other hazards**

vPvB Substances: None - PBT Substances: None

**Other Hazards:**

No other hazards















### SECTION 3. Composition/information on ingredients.

**3.1. Substances**

N.A.

**3.2. Mixtures**

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 45% - < 55%	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	 2.6/3 Flam. Liq. 3 H226  3.2/2 Skin Irrit. 2 H315  3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332
>= 15% - < 20%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336 EUH066
>= 15% - < 20%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4	 2.6/2 Flam. Liq. 2 H225  3.1/4/Inhal Acute Tox. 4 H332
>= 1% - < 3%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9	 2.6/2 Flam. Liq. 2 H225  3.7/2 Repr. 2 H361  3.10/1 Asp. Tox. 1 H304  3.9/2 STOT RE 2 H373  3.2/2 Skin Irrit. 2 H315  3.8/3 STOT SE 3 H336

### SECTION 4. First aid measures.

**4.1. Description of first aid measures**

**In case of skin contact:**

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

**In case of eyes contact:**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

## SUPER-SEALER NEW

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

### SECTION 5. Firefighting measures.

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

### SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

### SECTION 7. Handling and storage.

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

### SECTION 8. Exposure controls/personal protection.

8.1. Control parameters

xylylene - CAS: 1330-20-7

## SUPER-SEALER NEW

EU - LTE(8h): 221 mg/m<sup>3</sup>, 50 ppm - STE: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

n-butyl acetate - CAS: 123-86-4

ACGIH - LTE(8h): 150 ppm - STE: 200 ppm - Notes: Eye and URT irr

ethylbenzene - CAS: 100-41-4

EU - LTE(8h): 442 mg/m<sup>3</sup>, 100 ppm - STE: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

toluene - CAS: 108-88-3

EU - LTE(8h): 192 mg/m<sup>3</sup>, 50 ppm - STE: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - LTE(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

## SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Colorless liquid	--	--
Odour:	characteristic of solvent	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	24°C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	0,90 g/l	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--
VOC (Direttiva 1999/13/CE)	82,00 %		
VOC (carbonio volatile)	71,82 %		

## SUPER-SEALER NEW

### SECTION 10. Stability and reactivity.

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
None
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products  
None.

### SECTION 11. Toxicological information.

- 11.1. Information on toxicological effects  
Toxicological information of the mixture:  
N.A.  
Toxicological information of the main substances found in the mixture:
  - xylene - CAS: 1330-20-7  
LD50 (RAT) ORAL: 5000 MG/KG
  - ethylbenzene - CAS: 100-41-4  
LD50 (RAT) ORAL: 3500 MG/KG  
LD50 (RAT) ORAL: 4710 MG/KG BW
  - toluene - CAS: 108-88-3  
LD50 (RABBIT) SKIN: 14 G/KG (14000 MG/KG)  
LD50 (RAT) YOUNGADULTS ORAL: 5542 MG/KG BW

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard

### SECTION 12. Ecological information.

- 12.1. Toxicity  
Adopt good working practices, so that the product is not released into the environment.  
N.A.
- 12.2. Persistence and degradability  
N.A.
- 12.3. Bioaccumulative potential  
N.A.
- 12.4. Mobility in soil  
N.A.
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

### SECTION 13. Disposal considerations.

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### SECTION 14. Transport information.



- 14.1. UN number  
Not classified as dangerous in the meaning of transport regulations.  
ADR-UN number: 1866  
IATA-Un number: 1866  
IMDG-Un number: 1866
- 14.2. UN proper shipping name  
ADR-Shipping Name: RESIN SOLUTION  
IATA-Technical name: RESIN SOLUTION  
IMDG-Technical name: RESIN SOLUTION  
N.A.
- 14.3. Transport hazard class(es)  
ADR-Class: 3  
ADR-Label: 3  
IATA-Class: 3  
IATA-Label: 3  
IMDG-Class: 3  
N.A.
- 14.4. Packing group  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III  
N.A.
- 14.5. Environmental hazards  
Marine pollutant: No  
N.A.
- 14.6. Special precautions for user  
ADR-Tunnel Restriction Code: D/E  
IMDG-Technical name: RESIN SOLUTION  
IMDG-EMS: F-E, S-E  
N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
N.A.

#### Packaging:

**25 LT BUCKET -- APPROVAL 1A2/Y1,4/100 – Ø 31 cm x 45cmH – Weight 1,900 KG**

**10 LT BUCKET -- APPROVAL 1A2/Y1,6/120 – Ø 26 cm x 29cmH – Weight 0,960 KG**

### SECTION 15. Regulatory information.

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) n. 453/2010 (Annex II)  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.  
Regulation (EC) nr 648/2004 (detergents).  
1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

## SUPER-SEALER NEW

15.2. Chemical safety assessment  
No

### SECTION 16. Other information.

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- H225 Highly flammable liquid and vapour.
- H361 Suspected of damaging fertility or the unborn child.
- H304 May be fatal if swallowed and enters airways.
- H373 May cause damage to organs through prolonged or repeated exposure.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
- CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.