

## ARCHI-GO

### Multifunctional admixture for Architop®

---

#### **Description**

ARCHI-GO is a multifunctional powder for use with Architop® floors.

---

#### **Features**

ARCHI-GO considerably improves the workability of the mixture and facilitates the power-floating process. It makes it easier to obtain a close and compact surface and diminishes the occurrence of burn-outs. Use of this additive will speed up the application process.

---

#### **Uses**

ARCHI-GO is an additive for the preparation of the Architop® mixture.

---

#### **Application**

Ready to use. Thoroughly mix ARCHI-GO with Hardener then mix the powder with architop-catalyst according to the proportions given in the data-sheet.

---

#### **Technical Information**

See the safety data-sheet

---

#### **Consumption**

0,500 kg ARCHI-GO for a 25 kg bucket of Hardener.

---

#### **Packaging / Storage / Disposal**

Available in 10 kg buckets.

When stored in cool, dry environment the product will remain usable for up to 12 months.

---

#### **Warning**

Avoid contact with skin, nose, eyes etc. In case of accidental contact, wash thoroughly with soap and water and consult a doctor.

Consult the safety data sheet.

---

#### **IMPORTANT:**

All information contained in this data-sheet is based on the best practical and laboratory expertise. The customer is responsible for checking the product is suitable for use. The producer does not accept any responsibility arising from incorrect application. We recommend testing the products on small surfaces prior to use on the jobsite. This data-sheet replaces and annuls all previous versions. Data may be changed anytime. We also remind you that Ideal Work products are for professional use only and Ideal Work provides customers with training opportunities upon request. Whoever uses these products without authorisation shall take full personal responsibility and the outcome will be at their own risk.

EDITION01 dated 10.06.2020 - Rev. 00 dated