

ARCHITOP® CATALYST

Liquid catalyst for Architop® coating

Description

ARCHITOP CATALYST is a water-based copolymer liquid.

Features

Mixed with Color Hardener, ARCHITOP CATALYST creates the Architop® system. Architop® is an innovative 2-3 mm thick decorative cementitious flooring with exceptional resistance characteristics and a refined aesthetic.

Fields of use

ARCHITOP-CATALYST is the liquid component of the Architop® mixture.

Application

For mixing method and ratio, consult the ARCHITOP® technical sheet.

Technical data

Liquid ready-to-use.
Consult the safety data sheet.

Coverage

For mixing method and ratio, consult the ARCHITOP® technical sheet

Packaging / storage / disposal

ARCHITOP-CATALYST is supplied in 25 L jugs.
In its original packaging at a temperature between 5°C and 30°C it can be kept for at least 12 months. Avoid direct sunlight.

Warning

On very hot days, to lengthen the processing time, it is useful to keep ARCHITOP CATALYST in a cool place before and during use.
Do not swallow. Avoid contact with eyes.
Consult the safety data sheet.

IMPORTANT

All information contained herein is based on the best and most recently available practical and laboratory testing. It is the customers responsibility to determine that the product is suitable for their chosen application. The manufacturer assumes no responsibility for the results of incorrect applications. You should always test on a small area before full scale application. This document replaces all previous versions. The data can be changed at any time. Also note that the products are intended for professional use only. Ideal Work provides training, updates and refresher courses for their regular customers on request. Anyone using these products without being enabled does so at their own risk.

ED. 01 dated 17.03.2020 - REV. 00