

# **IDEAL CERA**

## Metallic wax . Acryl-polymer floor protection

## **DESCRIPTION**

IDEAL CERA is made of metallic acrylic polymers that give the floor a significant aesthetic effect as well as increased protection, making it self-polishing without the need for polishing machines.

IDEAL CERA will work on concrete, Micro-topping, Decorative Epoxy, Urethane or Ideal Sealers as a protective coating. The benefit of using Ideal Metallic Wax is to produce a sacrificial layer between foot traffic and the actual finished floor. IDEAL CERA is designed for long term surface protection for interior floor finishes. Working as a sacrificial layer to protect the underlying finished floor, Ideal Cera can be easily maintained and reapplied.

#### **FEATURES**

- □ Water-based product, non-toxic
- □ Excellent adhesion to substrate
- □ Easily restorable
- Apply with brush washcloth or spray

### PREPARATION OF THE SURFACE

The surface must be clean, healthy and free of loose particles and oil stains. It is recommended to wash the surface with a degreaser type Ideal Strong product before applying IDEAL CERA.

## **APPLICATION**

IDEAL CERA can be applied with a wax spreader, or airless pump. We recommend that two coats be applied. Dilution 1:1 with water.

#### **TECHNICAL INFORMATION**

APPEARANCE Milky white liquid FLASH POINT Non-flammable BOILING POINT >100°C SOLUBILITY in water SMELL Typical PH 8-8,5 circa

#### PACKAGING AND STORAGE

IDEAL CERA is available in 5 -10 - 25 I cans.

In the original packaging and when stored at 10-30°C, the product will last for 12 months.

### **CONSUMPTION**

About 25-40g/m<sup>2</sup>.



## **CLEANING OF TOOLS AND HYGIENE PRECAUTIONS**

- □ To clean tools, use only soap and water.
- $\hfill\Box$  It is recommended to wear gloves and a protective suit and eyewear.
- □ In case of contamination, wash with soap and water.
- $\ \square$  Spray in the eye should immediately be washed with running water for 10-15 minutes, then consult your doctor.

#### IM ORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - IST 0498 EDIT. 01 of 01 February 2014 Review 02 dtd 18/05/2018