

# HYDRO DEFENSE

cod. HYDRO DEFENSE0,5 N

## Protective water repellent

### DESCRIPTION

HYDRO DEFENSE0,5 N is a water-repellent water-based protective coating that increases the water repellence of Microtopping® surfaces.

### FEATURES

- Easy to apply over existing polyurethane coatings (Ideal PU 78 or WB EASY)
- Excellent adhesion to substrate
- 100% matt finish. It does not change the hue of the background

### FIELDS OF USE

It is recommended for Microtopping® surfaces in frequent contact with water, such as the walls of shower cubicles, sinks, kitchen countertops and other surfaces. It is not suitable for walkable surfaces.

Helps prevent the formation of limescale deposits on wet surfaces.

### APPLICATION

The surfaces for application must be dry, clean, free of any foreign substances and loose particles. We recommend washing the surface with IDEAL WORK PERFETTO detergent before application.

Apply HYDRO DEFENSE0,5 N evenly with a rag or brush. Typical application is 1 coat.

Wait at least 24 hours after application before using the treated surface.

The product can be reapplied after 6-18 months depending on the conditions of use.

### TECHNICAL INFORMATION

Consult the safety data sheet.

### CONSUMPTION

The consumption on a Microtopping® surface is about 20g/m<sup>2</sup>.

### PACKAGING / STORAGE / DISPOSAL

Available in 0,5 L packs. The product, if stored in a dry and ventilated place with temperatures between +5°C and +30°C, is guaranteed for 12 months.

### WARNING

After applying HYDRO DEFENSE0,5 N, no water-based products or resins can be applied to the surface.



**IMPORTANT**

The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is not used in accord with its instructions. The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is performed even partially in contrast with these guidelines or with products not covered by them.

The manufacturer also declines any responsibility for the aesthetic aspect of the flooring which depends on the installation methods, working times and climatic conditions of the site. The applicator must take these into account when scheduling and applying the materials supplied by the manufacturer.

The applicator notes that Ideal Work is in no way responsible for the suitability of the solution chosen in relation to:

A) Substrate suitability, climatic conditions or any other external parameter which may affect the performance of the Ideal Work products being used.

B) The stresses to which Ideal Work products may be put under operation.

It also notes that the indications provided by Ideal Work in its technical documentation are to be considered a necessary condition but do not in any way relieve the contractor of the responsibilities and technical evaluations of the applicator. The data can be changed at any time. Also note that the products are intended for professional use only.