

PRIMER WB

Acrylic mono-component water-based primer for Microtopping®, Lixio®, Lixio® Plus and other cementitious surfaces.

Description

PRIMER WB is an acrylic mono-component coating based on a non-yellowing water-based resin designed for the preparation of Microtopping®, Lixio®, Lixio® Plus and other cementitious surfaces before treatment with IDEALPU-WB EASY type resins.

Features

PRIMER WB exhibits high adhesion properties to clean and solid cement surfaces and provides an excellent bonding to successive coatings. Used in combination with IDEALPU-WB EASY, it forms an easy-to-use protection system that limits any aesthetic defects potentially resulting from roller applications.

Uses

- Microtopping® floors and claddings
- Lixio® and Lixio® plus
- Other decorative surfaces (contact our technical office)

For Architop® and Nuvolato floors please use the specific WB PRIMER MAX

Application

- PRIMER WB should be applied in a thin, uniform layer. It is recommended to provide good air circulation to improve the drying phase and film properties.
- PRIMER WB drying takes place by water evaporation. For proper film development, apply only when the surface temperature is above 10 °C, and the relative humidity (air) is below 80%.
- For better results dilute PRIMER WB with water:

on Microtopping add	10% of water
on Lixio® and Lixio® Plus add	20-30% of water

Technical Information

Overcoating time with IDEALPU-WB EASY (no grinding)	3-4 h (*)
Application temperature	+10°- +30°

(*) a 20° e 65% di UR

Consumption

Consumption 50 g/m² (undiluted product).

On Microtopping® add 10% of water.

On Lixio® and Lixio® Plus add 20-30% of water.

Packaging / Storage / Disposal

Available in 5,0 and 0,5 L tins.

Shelf-life of 12 months in fresh and dry storage in its original sealed packaging.

Avoid freezing. Do not store at temperatures below 5 °C.

Precautions

- Avoid skin and eye contact; it is harmful if swallowed.
- When used in closed areas provide appropriate ventilation.
- Product residues and empty containers are to be disposed of in compliance with the local rules in force.
- Clean the tools with water before the resin is dry.
- Do not keep food in the application area.
- Dispose leftovers of material.

Please refer to the safety sheet before use. (MSDS)

IMPORTANT

All information contained in this data-sheet is based on the best practical and laboratory expertise. The customer is responsible for checking the product is suitable for use. The producer does not accept any responsibility arising from incorrect application. We recommend testing the products on small surfaces prior to use on the jobsite. This data-sheet replaces and annuls all previous versions. Data may be changed anytime. We also remind you that Ideal Work products are for professional use only and Ideal Work provides customers with training opportunities upon request. Whoever uses these products without authorisation shall take full personal responsibility and the outcome will be at their own risk.

EDITION01 dated 10.06.2017 - Rev. 01 dated 28.11.2019