

IDEAL OPEN

Concrete cleaner and pore opener

DESCRIPTION

IDEAL OPEN is a product composed of a strong acid buffered by surfactants and anti-foaming. It attacks surfaces with the strength of the acid and removes dirt and grease with the power of a detergent.

Applied to concrete, it is designed to open the pores of the surface so as to allow any further processing of painting and floor protection. Its application on tile and clinker is designed to remove dirt and any concentration of lime.

It can be used as cleaner or to prepare concrete surfaces that will be treated with reactive stain IDEAL STAIN or protective sealers.

APPLICATION

IDEAL OPEN is applied diluted with water, dilution ratio of 1:5 (1 part of IDEAL OPEN with 5 parts water)

Apply with a floor machine or flooring buffer. Always check that there is no bare metal. Rinse thoroughly with clean water.

CONSUMPTION

100 g/m² of diluted product.

20 g/ m² of pure product.

PACKAGING AND STORAGE

IDEAL OPEN is available in 10 - 25 l tanks.

In the original packaging and when stored at 10-30°C, the product will last for 12 months.

TECHNICAL SPECIFICATIONS

CORROSIVE PRODUCT

PROTECT YOUR EYES, FACE AND SKIN

SENSITIVE TO COLD

FOR PROFESSIONAL USE ONLY

IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - IDEAL OPEN EDIT. 01 of 01 February 2011 Review 02 dtd 22/05/2015