

## IDEAL STRONG

### Strong degreasing agent

#### DESCRIPTION

IDEAL STRONG is obtained from pure raw materials. It is a strong alkaline degreasing agent suitable for all types of concrete, clinker, ceramic, tile, uncured terracotta, PVC and linoleum surfaces.

#### APPLICATION

It can be used pure or diluted with up to 75% water, depending on the level of dirt to remove. An optimal dilution ratio can be 1:10 (1 part of IDEAL STRONG with 10 parts water). Apply with a mop or floor machine. Rinse thoroughly with clean water.

#### CONSUMPTION

100 g/m<sup>2</sup> of diluted product.  
10 g/ m<sup>2</sup> of pure product.

#### PACKAGING AND STORAGE

IDEAL STRONG is available in 10 - 25 L tanks.  
In the original packaging and when stored at 10-30°C, the product will last for 12 months.

#### WARNINGS

As a dewaxing product, it cannot be used with metallised wax as it will remove it. It cannot be mixed with any other product as it is calibrated with highly alkaline mixtures.

Improper use with acid products could trigger dangerous decomposition reactions, releasing toxic-corrosive vapours.

Moreover, do not mix with bleach or sodium hypochlorite as chlorine could be released.

This product must always be handled with care, wearing latex, vinyl, neoprene or PVC gloves.

It is a caustic product; hence glasses should be used in case of contact to prevent serious damage to the eyes. In case of eye contact, rinse immediately eyes with plenty of water and call a physician, informing him/her that you have been in contact with a substance containing sodium hydroxide.

If swallowed, do not induce vomiting as the substance rising up to the oesophagus could be much more dangerous than if remained swallowed. A gastric lavage is necessary in these circumstances.

For further details, contact the poison centre of Milano-Niguarda.

#### IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - IDEAL STRONG EDIT. 01 of 01 February 2011 Review 02 dtd 22/05/2015