

IW-BLOCKER

Paste for blocking/fixing reinforcing mesh on various supports

Description

Single-component, ready to use, water-based paste for blocking/fixing reinforcing mesh on concrete, screed, plasterboard, ceramic tiles and other backgrounds.

Features

- Single-component
- Application temperature +10°C ÷ +40°C
- Application by roller or brush
- Ready to use – no mixing required
- Drying time to touch approximately 3h
- Re-application time approximately 3-6 hours
- For use only on internal surfaces.

Uses

- Fixing of reinforcing mesh on internal horizontal backgrounds;
- Fixing of reinforcement mesh on internal vertical backgrounds;
- Primer on plasterboard and plaster;

Application

Clean the substrate from any trace of oil, grease, wax or paint residues. The substrate must be free from cracks or loose, friable particles. Anhydrite screeds must be sanded before application of *IW BLOCKER*. Surface treatments such as waxes, resins and release agents must be completely removed. Do not apply when rising damp present. Spread *IW BLOCKER* on the surface evenly with a roller or brush. Install the glass-fibre mesh during the application of the product without overlapping or folds and do not overlap on joints. On absorbent surfaces (I.E. screed or plaster), first apply a coat of *IW BLOCKER* diluted with approximately 20% with water to help control absorption and then a second full strength coat whilst installing the mesh. *IW Blocker* can be applied on ceramic tiles on floors and walls, provided that the surface has been properly prepared by grinding to create a mechanical key.

It can be also used as a vertical primer for plasterboard or plaster.

Technical Information

Touch drying time:	3 h
Overcoating time:	3-6 h (depending on temperature)
Dilution:	Ready to use.
Application temperature:	between 10 and 40°C with under 80% HR

Consumption

Coverage, full strength, approximately 0,35 Kg/m²

Packaging / Storage / Disposal

Available in 5 kg tins.

Protect from freezing. Storage time in the original packaging approximately 12 months.

Precautions

Only for internal use.

Not suitable in the presence of rising damp.

Refer to technical data sheet

IMPORTANT

All information contained in this data-sheet is based on the best practical and laboratory expertise. The customer is responsible for checking the product is suitable for use. The producer does not accept any responsibility arising from incorrect application. We recommend testing the products on small surfaces prior to use on the jobsite. This data-sheet replaces and annuls all previous versions. Data may be changed anytime. We also remind you that Ideal Work products are for professional use only and Ideal Work provides customers with training opportunities upon request. Whoever uses these products without authorisation shall take full personal responsibility and the outcome will be at their own risk.

EDITION01 dated. 18-05-.2018 - Rev. 01 dated 31.08.2018