

IW-BLOCKER W

cod. IW-BLOCKER W

Water-based paste for blocking/fixing reinforcing mesh-WHITE

DESCRIPTION

Single-component, ready to use, water-based paste for blocking/fixing reinforcing mesh on concrete, screed, plasterboard, ceramic tiles and other backgrounds.

FEATURES

- Single-component
- Application temperature $+10^{\circ}\text{C} \div +40^{\circ}\text{C}$
- Application by roller or brush
- Ready to use – no mixing required
- Drying time to touch approximately 3h
- Re-application time approximately 3-6 hours
- For use only on internal surfaces.
- Not suitable for humid surfaces

USES

- Fixing of reinforcing mesh on internal horizontal backgrounds;
- Fixing of reinforcement mesh on internal vertical backgrounds;
- Primer on plasterboard and plaster;

APPLICATION

Clean the substrate from any trace of oil, grease, wax or paint residues. The substrate must be free from cracks or loose, friable particles. Anhydrite screeds must be sanded before application of IW-BLOCKER W. Surface treatments such as waxes, resins and release agents must be completely removed. Do not apply when rising damp present. Spread IW-BLOCKER W on the surface evenly with a roller or brush. Install the glass-fibre mesh during the application of the product without overlapping or folds and do not overlap on joints. On absorbent surfaces (I.E. screed or plaster, plasterboard...), first apply a coat of IW-BLOCKER W diluted with approximately 20% with water to help control absorption and then a second full strength coat whilst installing the mesh. IW-BLOCKER W can be applied on ceramic tiles on floors and walls, provided that the surface has been properly prepared by grinding to create a mechanical key.



TECHNICAL INFORMATION

Touch drying time:	3 h
Overcoating time:	3-6 h (depending on temperature)
Dilution:	Ready to use.
Application temperature:	between 10 and 40°C with under 80% HR

CONSUMPTION

Coverage, full strength, approximately 0,300 Kg/m²

PACKAGING / STORAGE / DISPOSAL

Available in 10 kg tins.

Protect from freezing. Storage time in the original packaging approximately 12 months.

PRECAUTIONS

Only for internal use.

Not suitable in the presence of rising damp.

Refer to technical data sheet

IMPORTANT

The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is not used in accord with its instructions. The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is performed even partially in contrast with these guidelines or with products not covered by them.

The manufacturer also declines any responsibility for the aesthetic aspect of the flooring which depends on the installation methods, working times and climatic conditions of the site. The applicator must take these into account when scheduling and applying the materials supplied by the manufacturer.

The applicator notes that Ideal Work is in no way responsible for the suitability of the solution chosen in relation to:

A) Substrate suitability, climatic conditions or any other external parameter which may affect the performance of the Ideal Work products being used.

B) The stresses to which Ideal Work products may be put under operation.

It also notes that the indications provided by Ideal Work in its technical documentation are to be considered a necessary condition but do not in any way relieve the contractor of the responsibilities and technical evaluations of the applicator. The data can be changed at any time. Also note that the products are intended for professional use only.