

MT-DEC

Retarding admixture for decorative Microtopping® on vertical surfaces.

Description

MT-DEC is a retarder specifically designed for use when creating vertical decorative textures with Microtopping® in particular when more working time is required to create textured finishes.

Features

MT-DEC mixed with FINISHING COAT improves its workability and slows its setting, thus providing sufficient time for the application of the desired Wall-texture.

Fields of use

Mixed with MT Finishing Coat for the creation of wall textures and vertical surfaces.

Application

MT-DEC powder must be carefully mixed dry with MT-Finishing Coat.

Only then add the polymer.

MT-DEC cannot be used for the construction of floors.

One pack of MT-DEC is sufficient for a complete bucket of MT-Finish Coat.

Packaging / storage / disposal

MT-DEC is available in 1.75 Kg pots, enough for one full MT FC bucket.

In the original packaging and at a temperature of between 5°C and 30°C, the product will remain usable for up to 12 months.

Warning

Avoid contact with skin, mucous membranes, eyes etc. In case of accidental contact, wash thoroughly with soap and water and consult a doctor.

Consult the safety data sheet.

IMPORTANT

All information contained herein is based on the best and most recently available practical and laboratory testing. It is the customers responsibility to determine that the product is suitable for their chosen application. The manufacturer assumes no responsibility for the results of incorrect applications. You should always test on a small area before full scale application. This document replaces all previous versions. The data can be changed at any time. Also note that the products are intended for professional use only. Ideal Work provides training, updates and refresher courses for their regular customers on request. Anyone using these products without being enabled does so at their own risk.

Ed 01 dated 14.12.2017 - REV. 01 dated 13.03.2020