

PRIMER-FF W

cod. PRIMER-FF W

Multi-purpose fine-grained adhesion primer

DESCRIPTION

Multi-purpose white fine-grained adhesion primer.

FIELDS OF USE

It is used as a bonding primer for particularly thin-film wall coatings like MICROTOPPING HP, TERRAE-CALCE FINO, SOLIDRO-TOP.

FEATURES

PRIMER-RR has excellent adhesion on plasterboard, concrete, brick, marble, ceramics, cement-based and gypsum-based renders. It is suitable for internal and external walls.

APPLICATION

The substrates must be clean, dry and free of oils, greases, cement mortars and loose particles. The support must be at least of level Q3. Pre-wetting of the substrate is not required. Mix before use and apply by roller, paint-brush, spray or spatula.

For use on plasterboard or poorly cohesive substrates, it is recommended to pre-apply a specific fixative or a coat of Ideal Binder diluted 1:1 with water

TECHNICAL INFORMATION

Specific weight	1.35 Kg/L
Toxicity	non-toxic
Minimum application temperature	10°C

CONSUMPTION

Consumption: 3-400 gr/m²

PACKAGING / STORAGE / DISPOSAL

PRIMER-FF W is supplied in 15,00 Kg tanks.

It can be stored for approximately 12 months in the original containers at a temperature between 5°C and 35°C.



WARNING

For good performance and workability, it is absolutely necessary for the substrate to be solid and free of any unstable parts or loose particles.

Consult the safety data sheets.

IMPORTANT

The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is not used in accord with its instructions. The manufacturer disclaims any responsibility for the achievement of the services declared for the system and for the success of the work if it is performed even partially in contrast with these guidelines or with products not covered by them.

The manufacturer also declines any responsibility for the aesthetic aspect of the flooring which depends on the installation methods, working times and climatic conditions of the site. The applicator must take these into account when scheduling and applying the materials supplied by the manufacturer.

The applicator notes that Ideal Work is in no way responsible for the suitability of the solution chosen in relation to:

A) Substrate suitability, climatic conditions or any other external parameter which may affect the performance of the Ideal Work products being used.

B) The stresses to which Ideal Work products may be put under operation.

It also notes that the indications provided by Ideal Work in its technical documentation are to be considered a necessary condition but do not in any way relieve the contractor of the responsibilities and technical evaluations of the applicator. The data can be changed at any time. Also note that the products are intended for professional use only.