

## SEAL STRIP

*Professional GEL paint remover*

---

### Description

SEAL STRIP is a mixture of organic solvents emulsifiable in water, specifically designed to remove traces of acrylic paints.

---

### Features

- Water-based, non-flammable
  - It doesn't contain toxic or dangerous atmospheric pollutants
  - Easy to clean with water and soap or denatured alcohol
  - Just barely perceptible smell
  - Slow evaporation for effective penetration
- 

### Fields of use

- Removal of resin treatments on industrial and decorative concrete floors
  - Removal of resins on printed floors
- 

### Application

SEAL STRIP is usually applied by roller, taking care to make a uniform and abundant application. Leave the product to work for about ten minutes and then wash with water and a buffer- machine.

---

### Technical Information

Application temperature 10°-25°

---

### Consumption

Coverage 0,2-0,4 Kg/m<sup>2</sup>

---

### Packaging / Storage / Disposal

It is available in 10 kg tins. Store only in plastic buckets.  
Protect from freezing. Storage time in the original packaging 12 months.

## Precautions

Make a test-try before application.

Refer to tecnica data sheet

---

### **IMPORTANT:**

All information contained in this data-sheet is based on the best practical and laboratory expertise. The customer is responsible for checking the product is suitable for use. The producer does not accept any responsibility arising from incorrect application. We recommend testing the products on small surfaces prior to use on the jobsite. This data-sheet replaces and annuls all previous versions. Data may be changed anytime. We also remind you that Ideal Work products are for professional use only and Ideal Work provides customers with training opportunities upon request. Whoever uses these products without authorisation shall take full personal responsibility and the outcome will be at their own risk.

EDITION 01 dated 05.02.2019 Rev. 00 dated

---