

## NEUTRALIZE

### Ph controller

#### DESCRIPTION

NEUTRALIZE is used to balance the level of alkalinity of concrete, allowing an optimal level of 7-10 pH to be reached. It is normally applied during the washing process, before and after the use of reactive stains and dyes

#### APPLICATION

The product can be spread in small quantities on the floor before washing or may be mixed with water. Let the product act for about 10 minutes then wash the surface with water.

#### CONSUMPTION

Indicative consumption 25 g/m<sup>2</sup>.  
With a pack (15 kg), about 600 m<sup>2</sup> can be covered.

#### PACKAGING AND STORAGE

15 kg pots

The product must be stored in a fresh and dry place in its original closed container.

#### IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - IST 0472 EDIT 01 of 01 February 2001 Review 01 dtd 22/05/2015