

LIQUID RELEASE AGENT

Liquid release agent for Ideal Wall, Ideal Tix or stampable overlay

DESCRIPTION

When applied to floor or wall stamps, LIQUID RELEASE AGENT prevents cement, cement mixture or mortar from causing damage both to stamps and to final products when falseworks are removed.

It also prevents stamps from being damaged by cement acidity, reclaiming the stamp rubber. LIQUID RELEASE AGENT is composed of aliphatic solvents added to a slow formulation fruity compound; its appearance is liquid and transparent with a particular smell.

APPLICATION

- Ready to use product.
- Apply by airless spraying or brush.

TECHNICAL SPECIFICATIONS

FLAMMABLE

KEEP AWAY FROM HEAT SOURCES

HARMFUL IF INHALED OR SWALLOWED

ONLY FOR PROFESSIONAL USE

NOTICE

Store in closed containers in a fresh and ventilated place. It can be stored for about 12 months in its original containers. Close immediately after use.

IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - LIQUID RELEASE AGENT EDIT. 01 of 01 February 2011 Review 02 dtd 22/05/2015