

## ANTISKID

### Charges for non-slip resin Ideal Sealer

#### DESCRIPTION

Highly wear-resistant fillers that, when added to IDEAL SEALER, give the surface high anti-slip characteristics. Ideal for protecting floors and pool edges of printed areas where non-slip properties are required.

#### APPLICATION

Mix a pack of ANTISKID in a pot of IDEAL SEALER (20 l) for 1-2 minutes in order to distribute loads evenly. Apply as usual; see IDEAL SEALER data sheet.

#### PACKAGING AND STORAGE

0.370 g containers.

The product should be stored in a dry and windy place, with temperatures no lower than 5° C. IDEAL WORK ensures that products used for production are totally free of defects. The product, if properly stored, is guaranteed for 12 months.

#### IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - ANTISKID of 01 February 2011 Review 03 dtd 22/05/2015